beamZ Pro

**IP65**

## NEUTRON-DOT
## OUTDOOR LINKABLE
## HYBRID FIXTURE

- High power warm white LED (2700K)
- Pixel-controllable RGB Aura backlight
- Compact and lightweight aluminium housing
- IP65 Rating, for indoor and outdoor use
- Beam angle of 23 degrees
- 16-bit PWM dimming
- Smart coupling system (2 pieces included)
- Control panel with OLED display
- Key lock option and possibility of reverse display
- Auto mode
- Intelligent cooling system
- Weatherproof connectors, DMX
  and Power Connector TR (in/out)
- For architectural and entertainment use

| 151.525 | CARTON 4 | PALLET 96 |
|---|---|---|
| **Light source** | | 3-in-1 LED, Single WW LED |
| **LED colours: Center LED** | | Warm White |
| **LED colours: Aura Ring** | | Red, Green, Blue |
| **LED power** | | 60W |
| **LED power: Backlight** | | 1W |
| **Quantity of backlight LEDs** | | 16 |
| **Colour temperature** | | 2700K |
| **Beam angle** | | 23° |
| **Illuminance** | | 61.331 lx @ 1m |
| **Flash rate per second** | | 0 - 20Hz |
| **RDM** | | Yes |
| **DMX channels** | | 1, 3, 4, 16, 64 |
| **DMX connection** | | 3-pin XLR |
| **IP rating** | | IP65 |
| **Cooling** | | Convection |
| **Power plug** | | P-Con TR1 |
| **Power consumption** | | 0.944 - 0.473A |
| **Power supply** | | 100-240VAC 50/60Hz |
| **Dimensions (L x W x H)** | | 142 x 142 x 218mm |
| **Weight** | | 2,30kg |

## NEUTRON-DOT
## BRACKET

- To mount 2 or 4 fixtures together

| 151.527 | CARTON 4 |
|---|---|

## NEUTRON-DOT
## FROST FILTER 60°

- Creates a 60° beam angle

| 151.528 | CARTON 16 |
|---|---|

## NEUTRON-DOT
## BARNDOOR

- Adjust light direction and width

| 151.529 | CARTON 16 |
|---|---|

## FL-DOT
## FLIGHTCASE

- Designed to fit 8 fixtures

| 151.526 | CARTON 1 | PALLET 12 |
|---|---|---|
| **Dimensions (L x W x H)** | | 630 x 610 x 255mm |
| **Weight** | | 17,60kg |

## NEUTRON-DOT
## COUPLING BLOCK

- To connect fixtures together

| 151.530 | CARTON 24 |
|---|---|